

APRIL 2013

Technical Information**Product for Professional Use Only****BRAYT S0 Marine - POLISHING COMPOUND
PROFFESIONAL****PRODUCT DESCRIPTION**

S0 Brayt a polishing paste is designed for professionals – manufacturers, shipyards and products where it forms the outer layer of the technical gelcoat or industrial topcoat with a high hardness. S0 removes imperfections after sanding grit sandpaper even P800 (depending on the hardness of the surface). Pasta is designed to work with machine. Machining with a maximum rotation speed 1800. Best applicators working with S0 are wool and hard sponges. We obtain a surface high gloss.

PHYSICAL AND CHEMICAL PROPERTIES

Density	1,3 kg/l
Colour:	White

APPLICATION

- Apply compound on the surface to be treated (use hard sponge or lambswool)
- Spread compound on the surface by machine with minimum RPM.
- Slowly increase the Speer to max. 1800 – 2000 RPM and polish surface with medium pressure.
- Polish surfaces until the scratches have been removed.
- Change applicator to a soft sponge and polish to reach perfect gloss.
- For increase shine effect please use polishing compound S2 BRAYT MARINE.

STORAGE

Product works best when its temperature is 15 – 25⁰C

Storage in sealed container at 0 – 45⁰C

WARRANTY PERIOD

12 months from production date